


GP 2240  
GP 2210  
EVOLUTION



Valvola a sfera Femmina-Femmina nichelata, con leva alluminio verniciata.

(\*) Nota: Le valvole da 2"1/2 - 3" - 4" sono con filettatura ISO 228/1 e vengono fornite con le leve smontate.



A

CODICE	Misura	A mm	øB mm	C mm	D mm	øE mm	gr	PN	Conf. pz/sc	Master pz/sc
<b>VERSIONE BLU</b>										
80001014	1/4"	45	26	47	85	10	140	50	36	144
80001038	3/8"	47	26	47	85	10	141	50	36	144
80001012	1/2"	56	31	49	85	15	175	50	36	144
80001034	3/4"	67	38	53	85	20	280	40	24	96
80001100	1"	80	46	63	105	25	460	30	12	48
80001114	1"1/4	94	57	69	105	32	675	25	8	32
80001112	1"1/2	103	68	86	135	40	987	25	4	16
80001200	2"	126	85	94	135	50	1650	16	4	16
80001212	2"1/2 (*)	127	110	119	240	64	3060	15	1	8
80001300	3" (*)	149	135	129	240	76	3970	15	1	6
80001400	4" (*)	185,5	164	153	300	100	7835	15	1	2
<b>VERSIONE ROSSA</b>										
86001014	1/4"	45	26	47	85	10	140	50	36	144
86001038	3/8"	47	26	47	85	10	141	50	36	144
86001012	1/2"	56	31	49	85	15	175	50	36	144
86001034	3/4"	67	38	53	85	20	280	40	24	96
86001100	1"	80	46	63	105	25	460	30	12	48
86001114	1"1/4	94	57	69	105	32	675	25	8	32
86001112	1"1/2	103	68	86	135	40	987	25	4	16
86001200	2"	126	85	94	135	50	1650	16	4	16
08007212	2"1/2 (*)	127	110	119	240	64	3060	15	1	8
08007300	3" (*)	149	135	129	240	76	3970	15	1	6
08007400	4" (*)	185,5	164	153	300	100	7835	15	1	2
<b>VERSIONE NERA</b>										
81001012	1/2"	56	31	49	85	15	175	50	36	144
81001034	3/4"	67	38	53	85	20	280	40	24	96
81001100	1"	80	46	63	105	25	460	30	12	48
81001114	1"1/4	94	57	69	105	32	675	25	8	32
81001112	1"1/2	103	68	86	135	40	987	25	4	16
81001200	2"	126	85	94	135	50	1650	16	4	16