

PRESE DA PARETE - IP44

Serie EUREKA

522.



512.



CUSTODIA DIRITTA

CUSTODIA INCLINATA

Poli	Hz.	Volt	Colore	h.	CUSTODIA DIRITTA		CUSTODIA INCLINATA	
					16A PG16/M20 10/50	32A PG21/M25 10/40	16A PG16/M20 10/50	32A PG21/M25 10/40
2P+T	50/60	100-130	Yellow	4	522.1650	522.3250	512.1650	512.3250
	50/60	200-250	Blue	6	522.1653	522.3253	512.1653	512.3253
	50/60	380-415	Red	9	522.1658	522.3258	512.1658	512.3258
	50/60	480-500	Grey	7				
	50/60	trasf.	Grey	12				
	>300-500	>50	Green	2				
3P+T	c.c.	>50-250	Grey	3				
	c.c.	>250	Grey	8				
	50/60	100-130	Yellow	4	522.1651	522.3251	512.1651	512.3251
	50/60	200-250	Blue	9	522.1654	522.3254	512.1654	512.3254
	50/60	380-415	Red	6	522.1656	522.3256	512.1656	512.3256
	60	440-460	Red	11				
	50/60	480-500	Grey	7				
	50/60	600-690	Black	5				
	50/60	380/440	Red	3				
	100-300	>50	Green	10				
	>300-500	>50	Green	2				
	3P+N+T	50/60	100-130	Yellow	4	522.1652	522.3252	512.1652
50/60		208-250	Blue	9	522.1655	522.3255	512.1655	512.3255
50/60		346-415	Red	6	522.1657	522.3257	512.1657	512.3257
50/60		480-500	Grey	7				
50/60		600-690	Black	5				
60		440-460	Red	11				
50/60		380/440	Red	3				
>300-500		>50	Green	2				

Serie OPTIMA-BASE

513.



513.

Serie OPTIMA-TOP



Poli	Hz.	Volt	Colore	h.	SAFE-IN		FAST WIRING	
					16A M20/M25 10/40	32A M32 1/10	16A M20/M25 10/40	32A M20/M25 10/40 M32 1/10
2P+T	50/60	100-130	Yellow	4	513.1650	513.3250	513.1650T	513.3250T
	50/60	200-250	Blue	6	513.1653	513.3253	513.1653T	513.3253T
	50/60	380-415	Red	9	513.1658	513.3258	513.1658T	513.3258T
	50/60	480-500	Grey	7			513.16536T	513.32536T
	50/60	trasf.	Grey	12			513.16533T	513.32533T
	>300-500	>50	Green	2			513.16532T	513.32532T
	c.c.	>50-250	Grey	3			513.16534T	513.32534T
	c.c.	>250	Grey	8			513.16538T	513.32538T
	50/60	100-130	Yellow	4			513.1651T	513.3251T
	50/60	200-250	Blue	9			513.1654T	513.3254T
	50/60	380-415	Red	6	513.1656	513.3256	513.1656TH	513.3256TF
	60	440-460	Red	11				
3P+T	50/60	480-500	Grey	7			513.16565T	513.32565T
	50/60	600-690	Black	5			513.16566T	513.32566T
	50/60	380/440	Red	3			513.16567T	513.32567T
	100-300	>50	Green	10			513.16564T	513.32564T
	>300-500	>50	Green	2			513.16561T	513.32561T
							513.16562T	513.32562T
							513.1652T	513.3252T
							513.1655T	513.3255T
	50/60	100-130	Yellow	4	522.1652	522.3252	512.1652	512.3252
	50/60	208-250	Blue	9	522.1655	522.3255	512.1655	512.3255
	50/60	346-415	Red	6	522.1657	522.3257	512.1657	512.3257
	50/60	480-500	Grey	7			513.1657TH	513.1657TF
50/60	600-690	Black	5			513.16576T	513.32576T	
60	440-460	Red	11			513.16577T	513.32577T	
50/60	380/440	Red	3			513.16575T	513.32575T	
>300-500	>50	Green	2			513.16574T	513.32574T	
						513.16572T	513.32572T	

Tensione nominale >50V
- Approvazioni da pag. 761

Morsetti a vite
 Morsetti a molla

Versioni disponibili anche con entrata cavi metrica.
Aggiungere "M" dopo il punto. Esempio: 522.M1650.

Maggiori informazioni pag. 110

Serie OPTIMA-BASE e Serie OPTIMA-TOP IP44:
pressacavo fornito di serie.