

Serie ISOLATORS



Poli	Dimensioni involucro (mm)	Grado di protezione	⌘	COMANDO DI EMERGENZA		USO GENERALE		COMANDO DI EMERGENZA		USO GENERALE	
63A	2	210x155x107	IP65	1/5	590.EM6302		590.GE6302				
	3				590.EM6303		590.GE6303				
	4				590.EM6304		590.GE6304				
80A	2	210x155x107	IP65	1/5	590.EM8002		590.GE8002				
	3				590.EM8003		590.GE8003				
	4				590.EM8004		590.GE8004				
100A	3	210x155x107	IP65	1/5	590.EM10003		590.GE10003				
	4				590.EM10004		590.GE10004				
125A	3	308x228x128	IP55	1/5				590.EM12503	590.GE12503		
	4							590.EM12504	590.GE12504		
160A	3	338x308x128	IP55	1/5						590.EM16003	590.GE16003
	4									590.EM16004	590.GE16004

■ DA PARETE - INVOLUCRO IN TECNOPOLIMERO - ATEX

Serie ISOLATORS-EX



Poli	Dimensioni involucro (mm)	Grado di protezione	⌘	COMANDO DI EMERGENZA		USO GENERALE	
20A	2	115x190x128	IP66	1/12	590.XEM2002		590.XGE2002
	3				590.XEM2003		590.XGE2002
	4				590.XEM2004		590.XGE2004
32A	2	115x190x128	IP66	1/12	590.XEM3202		590.XGE3202
	3				590.XEM3203		590.XGE3203
	4				590.XEM3204		590.XGE3204
40A	2	115x190x128	IP66	1/12	590.XEM4002		590.XGE4002
	3				590.XEM4003		590.XGE4003
	4				590.XEM4004		590.XGE4004